

Solutions for any
Application
Soluzioni per Tutte le
Applicazioni



Xylem ['ziləm]

- 1) The tissue in plants that brings water upward from the roots;
- 2) a leading global water technology company.

We're approximately 12,900 people unified in a common purpose: creating innovative solutions to meet our world's water needs. Developing new technologies that will improve the way water is used, conserved, and reused in the future is central to our work. We move, treat, analyze, and return water to the environment, and we help people use water efficiently, in their homes, buildings, factories and farms. In more than 150 countries, we have strong, long-standing relationships with customers who know us for our powerful combination of leading product brands and applications expertise, backed by a legacy of innovation.

For more information on how Xylem can help you, go to xylem.com.



Product Overview Gamma Prodotti



Legal head office
Xylem Water Solutions Italia Srl

Via Gioacchino Rossini 1/A
20020 - Lainate (MI) - Italy
Tel. (+39) 02 90358.1
Fax (+39) 02 9019990
www.xylemwatersolutions.com

For information and technical support
Xylem Service Italia Srl

Via Dottor Vittorio Lombardi 14
36075 - Montecchio Maggiore (VI) - Italy
Tel. (+39) 0444 707111
Fax (+39) 0444 491043
www.lowara.com

Xylem Water Solutions Italia Srl reserves the right to make modification without prior notice.
Lowara, Xylem are trademarks of Xylem Inc. or one of its subsidiaries.
© 2014 Xylem, Inc.

cod. 191020010 - P02/14



BOOSTER
GRUPPI DI PRESSIONE



Up To
Fino A

Power/Potenza: 132 kW
Capacity/Portata: 800 m³/h
Head/Prevalenza: 160 m

SURFACE
SUPERFICIE



Up To
Fino A

Power/Potenza: 355 kW
Capacity/Portata: 700 m³/h
Head/Prevalenza: 500 m

HVAC
CONDIZIONAMENTO
E RISCALDAMENTO



Up To
Fino A

Power/Potenza: 22 kW
Capacity/Portata: 610 m³/h
Head/Prevalenza: 89 m

BOREHOLE
SOMMERSE



Up To
Fino A

Power/Potenza: 350 kW
Capacity/Portata: 520 m³/h
Head/Prevalenza: 700 m

WASTE WATER
DRENAGGIO



Up To
Fino A

Power/Potenza: 7,5 kW
Capacity/Portata: 250 m³/h
Head/Prevalenza: 41 m

CONTROLLERS AND
VARIABLE SPEED DRIVE
CONVERTITORI DI
FREQUENZA E
CONTROLLI DI PRESSIONE



Up To
Fino A

Power/Potenza: 45 kW